



The Cityflex

- Ideal for smaller or difficult access jobs at more efficient cost
- Can clean up to 225mm diameter pipes
- Combined suction and jetting
- Optimum flow and pressure conditions
- Carries full Chapter 8 signing and guarding

A combined suction and jetting machine with a moving baffle to enable efficiencies due to fewer requirements to travel for water; has full remote control for all operational requirements. Also has 1 bar discharge pressure.



TANK CAPACITY	JETTING RATE
<ul style="list-style-type: none"> • 1000 gallons 	<ul style="list-style-type: none"> • 30 gallons / min at 3000 psi
WEIGHT	HIGH PRESSURE PUMP TYPE
<ul style="list-style-type: none"> • 7.5 Tonnes 	<ul style="list-style-type: none"> • High pressure piston pump
NORMAL LOADING TIME	HOSES
<ul style="list-style-type: none"> • 3 minutes 	<ul style="list-style-type: none"> • 130m Hydraulically Operated 3/4" hose reel • 200m Hydraulically Operated 1/2" hose reel
VACUUM RATE	VACUUM PUMP TYPE
<ul style="list-style-type: none"> • 2875 gallons / min 	<ul style="list-style-type: none"> • Wittig Rotary Vane 84dB • Air cooled, equipped with a lubrication pump
ODOUR CONTROL SYSTEM	
<ul style="list-style-type: none"> • Yes 	

Call today 01872 870086

email: info@clearflowltd.com

web: www.clearflowltd.com